Proc. 3rd Fed. Inter-Agency Sedimentation Conf. SEDIMENT-PHOSPHORUS RELATIONS IN SURFACE 73-41 thru 3-52.

RUNOFF FROM IRRIGATED LANDS

By D. L. Carter, Supervisory Soil Scientist, M. J. Brown, Soil Scientist, and J. A. Bondurant, Agricultural Engineer, Agricultural Research Service, Kimberly, Idaho.

ABSTRACT

Phosphorus and sediment concentrations were measured in irrigation and drainage waters, and phosphorus and sediment inflows and outflows comput-Relationships between phosphorus and sediment were developed. phosphorus and orthophosphate concentrations measured in nonfiltered samples are closely related to the sediment concentration, but dissolved orthophosphate measured in samples filtered through 0.45 µm membrane filters is independent of the sediment concentration. A net sediment inflow was found on one large tract where sediment settles in drains and the amount of surface runoff is low, but a net sediment outflow was found for another tract with steeper drains and from which more surface runoff returned to the river. Net phosphorus inflows were measured on both tracts. Particle size segregation takes place in irrigation and drainage waters whenever the flow velocity is slow enough to allo suspended sediment to settle, and the quantity of phosphorus per unit or sediment remaining suspended increases. Actually, much more phognorus settles with that portion of the sediment that settles than remains in suspension where sediments are eroded from silt loam or loam soils. Thus, conditions favoring settling are phosphorus conserving conditions.

INTRODUCTION

Phosphorus is tightly held by most soils and sediments, and the amount solubilizing, precipitating or combining with sediments depends upon equilibria conditions between the phorphorus in the ambient solution and that attached to or held by sediments. Sediments may scavenge phosphorus from solution (Taylor and Kunishi, 1971), and many sediments have a great capacity to do so (Latterell, Holt, and Timmons, 1971). Sediments also represent a vast phosphorus reservoir that can maintain a low and nearly constant water-soluble phosphorus concentration in a lake or stream for a very long time.

*Sediments carry large quantities of phorphorus into waterways each year as a result of erosion (Viets, 1971; Wadleigh, 1968). Phosphorus is a limited, valuable, natural resource required by all living organisms, and reclaiming it from ocean and lake sediments would be extremely expensive. Therefore, the phosphorus entering waterways ultimately reaching the ocean or other large water bodies represents a phosphorus loss to man, animals, and plants, except those living in aquatic environments.

Irrigated agriculture involves very complex and dynamic solution-to-solid phase equilibria for phosphorus. Irrigation waters from rivers and streams carry sediment loads and associated phosphorus that vary through the sea-These waters have a dissolved phosphorus concentration that may also vary during the season. When this water is applied to close growing crops, like alfalfa and grass, the sediment and the associated phosphorus is usually deposited upon the land. Dissolved phosphorus is effectively removed from the water that percolates through the soil (Carter, Bondurant, and Robbins, 1971; Carter, Robbins, and Bondurant, 1973). when the water is applied to recently cultivated row crops, the soil may erode adding to the sediment and associated phosphorus loads in the run-Surface and subsurface drainage waters from fields of various off water. crops may enter surface drains and mix. In some cases flow velocities in drains are low or the water is passed through a sediment pond and sedi-In other cases, the flow velocity is high and there is no ments settle. settling until the water reaches a river or a reservoir along a river, or in some cases, the ocean. All these dynamic processes can influence phosphorus equilibria.

During the past 6 years, we have been studying phosphorus inflows in the irrigation water and outflows in the drainage water from large irrigated tracts, and phosphorus-sediment relationships in irrigated agriculture in an effort to determine the extent of phosphorus losses from irrigated lands and to develop information useful for reducing such possible losses. This paper reports phosphorus and sediment concentrations in irrigation and drainage waters for two large tracts, functional relationships between sediment and phosphorus concentrations in irrigation and surface runoff waters, phosphorus inflows and outlides for two large tracts, phosphorus:sediment rations, and related information.

MATERIALS AND METHODS

The studies involved the 82,030 ha (202,700 a) Twin Falls Canal Company tract and the 65,350 ha (161,480 a) Northside Canal Company tract and the sampling sites previously described (Brown, Carter, and Bondurant, 1974). Three samples were collected at 2-week intervals at each site. They a 200 ml sample filtered through a 0.45 µm membrane filter immediately upon sampling, (2) a 200 ml nonfiltered sample, and (3) a 10 liter nonfiltered sample. Biological activity was stopped by adding 40 mg HgCl./liter immediately as samples were collected. The 200 ml samples were refrigerated at 4 C until analyzed. The 10 liter samples were allowed to settle for 1 week in the laboratory, and then the supernatant was siphened off and analyzed for phosphorus concentration. The sediment and a small amount of solution were transferred to weighed containers, dried at 105 C and weighed to determine sediment concentrations. The settling time exceeded that needed for 1.0 µm particles to settle the depth of the sample according to Stokes law. All samples were collected at a drop structure, culvert or turbulent zone to assure that the samples properly represented the atream and its sediment load. At some sites a fractional water-sediment sampler was used to assure representative samples (Heinemann and Brown, 1972);

All samples were analyzed for dissolved and total orthophosphate, dissolved and total hydrolyzable phosphorus and total dissolved and total phosphorus following chemical treatments previously described (Carter, et al., 1974). Dissolved organic and total organic phosphorus concentrations were obtained by subtracting orthophsophate plus hydrolyzable phosphorus from total phosphorus for the dissolved and total categories. The chemical treatments used were essentially those recommended by the Environmental Protection Agency (Environmental Progection Agency, 1974). Phosphorus concentrations were measured in the solutions following chemical treatment by the ascorbic acid method (Watanabe and Olsen, 1965). The pH was adjusted before adding the ascorbic acid-ammonium molybdate solution containing potassium antimony tartrate to assure reproducible results (Carter, et al., 1974).

Regression and correlation analysis were employed to evaluate sediment-phosphorus relations in irrigation and surface runoff waters. Such analyses were completed for dissolved orthophosphate and total phosphorus only because as studies progressed, hydrolyzable and organic phosphorus concentrations in irrigation and drainage waters seemed insignificant.

Sediments collected from the 10 liter samples were analyzed for total phosphorus by suspending 0.1 g subsamples in 40 ml of distilled water and following the persulfate digestion procedure for water samples (Carter, et al., 1974; Environmental Protection Agency, 1974). NaCHO extractable phosphorus was determined by extracting 5 g samples with 100 ml 0.5 M NaHCO solution and determining the phosphorus concentration by the ascorbic acid method (Watanabe and Olsen, 1965). Where only small amounts of sediments were obtained, 0.5 g of sediment was extracted with 10-ml of the solution.

Sediment, dissolved orthor asphate and total phosphorus inflows in the irrigation water and outflows in the surface drainage water were calculated for a typical irrigation season for the two tracts. This was done by multiplying the phosphorus and sediment concentration for each 2-week sampling period by the quantity of flow for that period and accumulating the results for the season.

不是一个人,我们就是我的人,我们就是我们的人,我们就是我们的人,我们就是我们的人,我们就是我们的人,我们的人,我们的人,我们的人,我们也是我们的人,我们们的人,我们

The relationship of phosphorus concentration to particle size was investigated by collecting samples from the surface 15-cm of field soils from certain subbasins in the two tracts, mixing soil samples with water without the aid of dispersing reagents, and allowing samples to settle for the time periods that gave an aggregate or particle size segregation into sand, silt, and clay sizes. This segregation was assumed to simulate processes taking place as eroded soil enters drainage streams and subsequently settles as the flow velocity decreases. Complete dispersion was not expected under these conditions, and some aggregates containing clay settled in the sand and silt fractions. These size fractions were analyzed for total- and NaHCO₃-extractable phosphorus. Surface soil samples were collected from both tracts on a grid and analyzed for total and NaHCO₃ extractable phosphorus so that results could be compared with those from

Table 1. Numbers of samples with sediment and phosphorus concentrations in specific ranges.

Variables				Nı	Numbers of Samples	Samples				
Sediment	0-50	51-100	0-50 51-100 101-200 33 21 32		Concentra -500 501-	Concentration Range (ppm) 500 501-1001 1001-2000 3 7 2	Concentration Range (ppm) 201-500 501-1001 1001-2000 Above 2000 13 7 2 3	ove 2000		
	0-25	0-25 26-50	51-75	76–100	Concentration 101-150	Concentration Range (ppb) 101-150 151-200 201-25	Concentration Range (ppb) 76-100 101-150 151-200 201-250	251-300	301-400	301-400. Above 400
Phosphorus* Ortho-P (F) Ortho-P(NF) Total-P(NF)	21	23	25% 14 1	23 14	20 24 19	7 70 70 70	7 . 22	10	5 17	11 16
*Ortho-P(F) is the orthophosphate measured in a sample filtered throu Ortho-P(NF) is the orthophosphate measured in a nonfiltered sample. measured in a nonfiltered sample.	is the	s the orthophosphat is the orthophospha a nonfiltered sampl	phosphate ophosphated	te measu ate meas le.	red in a ured in a	sample fi nonfilte	iltered th	rough a 0.	.45 µm men P 1s the	*Ortho-P(F) is the orthophosphate measured in a sample filtered through a 0.45 µm membrane filter. Ortho-P(NF) is the orthophosphate measured in a nonfiltered sample. Total-P is the total phosphorus measured in a nonfiltered sample.

sediments collected from surface drainage streams. Additional evidence that particle size segregation takes place in drainage streams was obtained by calculating phosphorus:sediment ratios (the quantity of phosphorus per unit of sediment) for some drainage streams with flow yelocities slow enough to allow settling and some with high flow yelocities so that there was little or no settling. Dissolved orthophosphate concentrations were subtracted from the total phosphorus concentrations so that the phosphorus involved was that attached to the sediment.

RESULTS AND DISCUSSION

The sediment concentration in surface runoff water returning to the river from the two large irrigation tracts varied widely during the irrigation season (Table 1). The lowest concentration measured was 10 ppm in the W drain on the Northside tract in which the flow velocity was very slow allowing the drain to serve as a sediment retention basin. The highest concentration measured was 2610 ppm in the J-8 drain on the Northside tract, but concentrations as high as 2250 ppm were measured in the Filer drain on the Twin Falls tract. Generally, the sediment concentrations were highest during the period when row crop cultivations were most frequent. After July, sediment concentrations were lower in all drainage water entering the river, except from those drains where the flow velocity was slow enough to allow sediments to settle. Little changes were observed in these drains.

The total phosphorus concentration paralleled the sediment concentration (Table 1). The relationship between the two parameters is given by the first equation in Table 2. A similar relationship was found between the

Table 2. Regression equation and correlation coefficients showing relationship between sediment and phosphorus concentrations in irrigation and drainage waters.

のであっていい。 「「「「「「「」」」、「「「」」、「「」」、「「」」、「「」」、「」」、「「」」、「」」、「」」、「」」、「「」」、「」」、「」」、「」」、「」」、「」」、「」」、「」」、「」」、「」」、「」」、「」

•				
X	Y .	Equation	r ²	r
Sediment in nonfiltered samples (ppm)	Total phosphorus in nonfiltered samples (ppb P)	Y = 140.52 + 0.72X	0.89	0.94
Sediment in nonfiltered samples (ppm)	Orthophosphate in nonfiltered samples (ppb P)	Y = 79.82 + 0.579X	0.90	0.95
Sediment in nonfiltered samples (ppm)	Orthophosphate in filtered samples (0.45 um) (ppb P)	Y = 57.71 + 0.033X	0.10	0.32

sediment and the orthophosphate concentrations determined in nonfiltered These results showed that the concentration of both orthophosphate and total phosphorus in nonfiltered water samples depends upon the sediment concentration. These equations could be used to predict the total phosphorus and orthophosphate in nonfiltered samples. Better predictive equations could likely be developed for specific surface drains or subbasins where conditions are more uniform. The third equation shows that there is no such relationship between the orthophosphate in filtered samples and the sediment concentration. Thus, the dissolved orthophosphate concentration is independent of the sediment concentration. solved hydrolyzable and organic phorphorus concentrations are very low in the 111 water samples included for comparison. Only two samples had dissolved hydrolyzable concentrations above 26 ppm and only four samples had organic phosphorus concentrations above that value. Total hydrolyzable and organic phosphorus concentrations were somewhat higher and related to the sediment concentrations, but still of little significance in irrigation and drainage waters.

There was a net sediment outflow or loss of 37,790 mt (41,368 t) from the Twin Falls tract or 0.46 mt/ha (0.20 t/a), in contrast to a net sediment inflow or accumulation of 45,170 mt (49,807 t) into the Northside tract or 0.69 mt/ha (0.30 t/a) (Table 3). These two tracts had contrasting results because of different amounts of surface drainage returning to the river and different slopes and resulting flow velocities in surface drains on the two tracts (Brown, Carter, and Bondurant, 1974). The surface drains on the Northside tract were constructed to a low slope, some of which serve effectively as sediment retention basins. One drain passes through a basin. The drains on the Twin Falls tract are mostly natural, steep channels in which the flow velocity is too high to allow much sediment settling.

Net total phosphorus and dissolved orthophosphate inflows were found for both tracts even though there was a net sediment outflow on the Twin Falls tract (Table 3). These results include only the phosphorus in the irrigation and surface drainage water, and do not include the phosphorus fertilizer applied to the land. The results indicated that the sediment leaving the Twin Falls tract carried less phosphorus per unit of sediment than the sediment entering the tract in the irrigation water. The sediment in the irrigation water was likely composed of smaller-sized particles than was the sediment leaving the tract in the surface drainage water.

The NaHCO₃ extractable and total phosphorus concentrations were greater in sediments in drainage waters from the Northside tract than that from the Twin Falls Tract (Table 4). These results show that more particle size segregation takes place in Northside tract drains than in Twin Falls tract drains. The sediment remaining suspended in Northside tract drains contained relatively more clay than that in Twin Falls tract drains. Both total and NaHCO₃ extractable phosphorus concentrations in sediments from both tracts were higher than concentrations found in surface soils, but the difference was greater for the Northside tract (compare tables 4 and 5).

Water, Sediment, dissolved ortho-P and total-P inputs and outputs for two large tracts for an irrigation season. Table 3.

			Metric			ij	English	
	Water	Sediment	Ortho-P	Total-P	Water	Sediment	Ortho-P	Total-P
	Ħ OT	1		768411441	a ft		t	
Inflow	Twin	Falls Tract	ict (82,030	ha)		(202,700	a)	
Diverted water	138,310	75,820	28.57	189.00	1,121,000	83,576	31,49	208,36
Rock Creek	13,930	43,090	12,11	34.84	112.932	47.502	13,85	47.87
Cedar Draw	4,144	8,750	2.82	11.16	33,595	9,647	3.10	12.48
Filer Drain	1,084	11,280	1.13	10.16	8,971	12,434	6.22	18.16
Mud Creek	7,239	13,820	5.64	16.47	58,684	15,236	1,92	7.87
Deep Creek	4,732	5,630	1.74	7.14	38,363	6,208	1.25	11.25
13 small drains	6,295	31,040	2.31	15.06	51,036	34,217	2.55	16.60
Net Inflow	100,866		2.82	94.17	817,599	4	2.60	99.18
Net Outflow	!	37,790	1.		1	41,368	}	1
Inflow	Nort	Northside Tract	t (65,350 ha	ha)		(161,480	a)	
Diverted water Outflow	150,631	57,250	34,38	159.39	1,221,182	63,111		175.70
×	1,410	1,300	1.28	3.75	11,432	1,431	1.42	4.13
N-32	2,478	2,160	1.84	5.71	20,087	2,375	2,02	6.29
ر. 1	622	. 3,550	0.25	1.42	5,039	3,911	0.28	1.56
w	1,780	3,440	09.0	2.97	14,432	3,798	0.67	3.27
W-26	1,787	1,280	0.25	1.19	14,488	1,405	0.49	4.72
W	096	350	0.45	4.28	7,779	384	0.28	1,31
Net Inflow	141,594	45,170	29.97	140.08	1,147,925	49,807	32.74	154.42
Net Outflow	{ []	}		-	1	!	!	1

pumped from wells for industrial purposes. Surface runoff totalled 14% of the total water inflow *Includes flow from subsurface drainage tunnels that enter the listed streams as well as water to the tract (Carter, Bondurant and Robbins, 1971)

		NaHC	NaHCO ₃ Extr	ract able	actable P (ppm	(i)			Total P	P (ppm)		:
Source		May	Jun	Jul	Aug	Sep	May	Jun	Jul	Aug	Sep	
						Northside	ide tract	-	,			
Diverted water	\$-1 01	138	80	46	ţ	1	1,100		1,040	1,100	1,278	
X	t }	195	148	86	95	61	1,206	1,040	1,036	1,185	.1,018	
N-32		345	277	104	1	72	1,395		1,076	1,338	941	
	,	47	75	59	7	89	649		1,018	1,110	876	
))		166	157	62	53	9	1,075		996	666	806	
W-26		171	191	55	77	64	1,345		985	1,018	940	
M.		278	404	1	:	318	1,370		1,000	1,228	1,006	
						Twin F	Falls tract					
Diverted water	1-	133	. 1	99	37	63	1,160		1,040	1,025	1,047	
Rock Creek	ا اند اند	36	122	38	28	33	955	. •	831	672	939	
Cedar Draw		; ;;	7,4	77	36	දි	895	•	905	915	819	
Filer Dra	i i	21	52	33	29	당	895		842	940	952	
Mud Creek	ł	ဓ္က	87	77	26	22	1,040		1,040	1,138	926	
Deep Creek	ين.	99	96	70	28	38	912		602	840	870	
Hansen Drain	aîn	36	95	32	28	41	882		870	970	988	
Kimberly Drain	Drain	54	59	70	38	8	963		897	912	965	

Table 5. NaHCO₃-extractable and total phosphorus concentration in soil samples collected from the surface 15 cm (6 in.) of fields in two large irrigation tracts, ppm (Carter, et al., 1974).

)	, , , , , , , , , , , , , , , , , , , ,	NaHCO,	Extra	ctable	P	*. · · · · · · · · · · · · · · · · · · ·	Tot	al P	
	No. of fields sampled	Max.	Min.	Med.	Mean	Max.	Min.	Med.	Mean
Northside tract	44	64	4	22	24	885	488	763	722
Twin Falls tract	48	55	6 .	20	22	1007	580	842	839

The relative total and NaHCO₃ extractable phosphorus concentration in the sand, silt, and clay size fractions of soils separated without the aid of dispersion agents are presented in Table 6. A comparison of the values in Tables 4 and 6 shows that particle size segregation is more complete in drains on the Northside tract than in drains on the Twin Talls tract as suggested earlier, because both total and NaHCO₃ extractable phosphorus concentrations in sediments from Northside tract drains are closer to the values for the clay size fraction separated from soils. Also, the data in Table 4 indicate that sediments in the diverted water are comprised mostly of clay which is as expected because the river water is stored in upstream reservoirs where settling can occur, and is then released for irrigation downstream as the demand requires.

Table 6. Total and NaHCO₃-extractable phosphorus for various particle and aggregate size fractions of surface soils collected from four subbasins, ppm (Carter, et al., 1974).

	Total P		NaHCO,	-extract	able P
Sand	Silt	Clay	Sand	Silt	Clay
875	1000	1400	33	55	137
650	97 5	1285	13	27	67
550	1150	1285	21	74	125
450	1020	1325	8	45	70
	875 650 550	Sand Silt 875 1000 650 975 550 1150	Sand Silt Clay 875 1000 1400 650 975 1285 550 1150 1285	Sand Silt Clay Sand 875 1000 1400 33 650 975 1285 13 550 1150 1285 21	Sand Silt Clay Sand 3 Silt 875 1000 1400 33 55 650 975 1285 13 27 550 1150 1285 21 74

The data in Table 7 show that the phosphorus: sediment ratio (the quantity of phosphorus per unit of sediment) indicates the extent of the particle size segregation. The higher the value of the ratio the more extensive was the particle size segregation. For example, ratio values for the W drain which serves as a sediment basin were 1.60 and higher. Values for the K drain which passes through a sediment retention basin also generally exceeded 1.0. When the flow velocity was too high to allow settling, as in the Filer drain, the values were generally less than unity. Values for Rock Creek and Deep Creek varied because their flows vary widely and

Table 7. The quantity of phosphorus per unit of sediment in irrigation and drainage waters.

		Sampl	ing dat	te, 1971	L			
	6/15	6/29	7/13	7/26	8/10	8/28	9/8	9/28
	Pho	sphorus	per uni	it of se	diment	X 100	00	
Northside Canal	2.24	1.60	1.42	1.60	1.97	3.14	2.97	3.24
Twin Falls Canal		0.75	1.96	2.39	2.21	2.77	3.13	2.93
A	1.78	3.40	1.60	2.67	3.45	3.45		2.65
ĸ	1.12	0.94	1.62	2.31	1.82	2.25	2.40	4.08
Filer	0.83	0.57	0.96	0.58	0.81	0.87	0.85	1.29
Rock Creek	0.81	1.04	0.87	1.09	0.60		1.45	1.17
Deep Creek	1.24	0.95		1.00	1.34	0.81	1.02	0.91

and the amount of settling is related to the flow velocity which is a function of the flow volume. The mean value for the total phosphorus for the Northside and Twin Falls tract surface soils, calculated in the same manner as for sediments were 0.72 and 0.84, respectively. Dividing values for each tract into those presented in Table 7 for drains of the respective tracts is another method of indicating the extent of particle size segregation. The numbers presented in Table 8 are particle size segregation indices. When these values exceed 1.0, particle size segregation has taken place, and the greater the number, the more extensive was the particle size segregation.

Table 8. Indices of particle size segregation in surface drainage streams.

	-		Samplin	g date,	1971			
Drain	6/15	6/29	7/13	7/26	8/10	8/24	9/8	9/28
W	2.5	4.7	2.2	3.7	4.8	4.8		3.7
K	1.6	1.3	2.2	3.2	2.5	3.1	3.3	5.7
Filer	1.0	0.7	1.1	0.7	1.0	1.0	1.0	1.5
Rock Creek	1.0	1.2	1.0	1.3	0.7		1.7	1.4
Deep Creek	1.5	1.1		1.2	1.6	1.0	1.2	1.1

The data presented in Tables 7 and 8 were obtained over a broad range of soil and cropping conditions, and varying stream sizes. Greater precision could likely be attained by restricting measurements to given stream sizes, subbasins, soils, cropping conditions, land slopes, time of season, etc. Also, in our studies, there was considerable variation in the total phosphorus measured in the surface soil so the numbers should be used only as indicators not as precise measures. Also sometimes canal water is spilled into surface drains, and the index values could

exceed unity because values of the phosphorus: sediment ratios in the irrigation water were generally greater than found in the surface soils.

Most of the sediment and associated phosphorus entering irrigated tracts is filtered from the water by soil as the water enters the soil or by close growing crops. Only a small fraction of that sediment entering an irrigated tract leaves that tract in drainage water, because only a small portion, 6% and 14% for the two tracts studied, applied water bebecomes surface runoff. Essentially all the sediment leaving an irrigated tract is from erosion of that tract, supplying different sediments in the drainage water than entered in the irrigation water.

CONCLUSIONS

Most of the phosphorus in irrigation water and surface drainage waters from irrigated lands is associated with or attached to the sediment. The total phosphorus concentration is directly related to the sediment concentration as is the orthophosphate measured on nonfiltered samples. Therefore, controlling the quantity of sediment returning to a stream from irrigated land controls to a large extent the quantity of phosphorus returning. The dissolved orthophosphate concentration is independent of the sediment concentration.

Sediment and phosphorus losses from irrigated tracts can be controlled by limiting the surface drainage water leaving the tract and by utilizing sediment retention basins or drains of low slope so that the flow velocity is slow enough for sediment to settle. Whenever the flow velocity is slow enough to allow settling, particle size segregation takes place. The clay size particles settle slowest and are most likely to be carried by the drainage stream to the river. These smaller particles contain higher phosphorus concentrations per unit weight so that as settling takes place the phosphorus per unit of sediment remaining in suspension In a sense, this is phosphorus enrichment of the suspended sediment. However, in sediments eroded from most silt loam or loam soils the amount of phosphorus associated with the sediment that settles greatly exceeds the amount associated with the smaller size particles remaining in suspension so that conditions favoring settling are conservation conditions for both sediment and phosphorus. Ideally, preventing surface runoff from entering a river would prevent all of the sediment loss and the only phosphorus loss would be the very small quantity in subsurface drainage water.

REFERENCES

Brown, M. J., Carter, D. L., and Bondurant, J. A., 1974, Sediment in irrigation and drainage waters and sediment inputs and outputs for two large tracts in southern Idaho. J. Environ. Qual., 3, 347-351. Carter, D. L., Bondurant, J. A., and Robbins, C. W., 1971, Water-soluble NO₃-N, PO₄-P, and total salt balances on a large irrigation tract, Soil Sci. Soc. Am. Proc., 35, 331-335.

- Carter, D. L., Brown, M. J., Robbins, C. W., and Bondurant, J. A., 1974, Phosphorus associated with sediments in irrigation and drainage waters for two large tracts in southern Idaho, J. Enyiron. Qual., 3, 287-291.
- Carter, D. L., Robbins, C. W., and Bondurant, J. A., 1973, Total salt, specific ion and fertilizer element concentrations and balances in the irrigation and drainage waters of the Twin Falls tract in southern Idaho, USDA, ARS-W-4.
- Environmental Protection Agency, 1974, Methods for chemical analysis of water and wastes, 249-263.
- Heinemann, W. H., and Brown, M. J., 1972, Fractional water-sediment sampler, Soil Sci. Soc. Am. Proc., 36, 376-377.
- Latterell, J. J., Holt, R. F., and Timmons, D. R., 1971, Phosphate availability in lake sediments, J. Soil and Water Conserv., 26, 21-24.
- Taylor, Alan W., and Kunishi, Harry M., 1971, Phosphate equilibria on stream sediment and soil in a watershed draining an agricultural region, J. Agr. Food Chem., 19, 827-831.
- Viets, Frank G., Jr., 1971, Fertilizers, J. Soil and Water Conserv., 26, 51-53.
- Wadleigh, C. H., 1968, Wastes in relation to agriculture and forestry, USDA Misc. Publ. No. 1065.
- Watanabe, F. S., and Olsen, S. R., 1965, Test of an ascorbic acid method for determining phosphorus in water and NaHCO₃ extracts from soil, Soil Sci. Soc. Am. Proc., 29, 677-678.